



B1531 SPECIFICATIONS


Versions: V20200312

Parameter		Value
Physical Parameter	Pixel Configuration	DIP570
	Pixel Pitch (mm)	15.625x31.25
	Pixel matrix per panel	8x96
	Pixel density (pixels/sq.m.)	2048
	Cabinet Dimensions (LxWxH)/ (mm)	250x1500x65
	Module Dimensions (LxWxH)/ (mm)	\
	Transparency Rate	70.00%
	Panel material	Aluminum profile
	Cabinet weight (kg/panel)	4.1
	Module weight (kg/panel)	\
Electronic Parameter	Color Grayscale (Bit)	16bit
	Gray Scale per Color (level)	65536
	Refresh Rate (Hz)	3840
	Driving Type	static
	Signal Transmission Distance (m)	CAT5 cable: <100 m; Single mode fiber: <10 km
Optical Parameter	Brightness (nit)	7000
	Optimal Horizontal Viewing Angle (°)	110
	Optimal Vertical Viewing Angle (°)	55
Electrical Parameter	AC Input Voltage (V)	AC: 100-240V±10%
	AC Input Frequency (Hz)	50-60
	AC Input Power Maximum Value (W/m ²)	400
	AC Input Power Typical Value (W/m ²)	133
Circumstance Parameter	Storage Temperature (°C)	-40 -70
	Working Temperature (°C)	-40-50
	IP rating (Front/Rear)	IP65/IP65
	Storage Humidity (RH)	10%~90%
	Working Humidity (RH)	10%~90%
	Lifetime Typical Value (hrs)	100000
Installation Type	Cabinet installation type	Fix
	Rigging Quantity (Vertical) (PCS)	\

If the parameter variation causing by product upgrades, all interpretation right belongs to Kingaurora.



B1531 dimensional drawing





B1531 pictures

